

# WESTERN TRUCK & TRAILER SALES INC.

**Sales, Finance & Rentals**

1885 South 900 West  
Salt Lake City, UT 84104

**(800) 869-4121**

**Parts & Service**

1490 South 400 West  
Salt Lake City, UT 84115

**PARTS**  
**WesternTruck.com**

**ONLINE**



## CPS NEVADA BOTTOM DUMP TRAIN 2-2-2



### SPECIFICATIONS

- 2-Axle Lead:  
Model 4B240A200
- 4-Axle Pup:  
Model 4B224A200
- 37 CU YD Capacity
- 64' OAL
- 96" Wide
- Hopper Height: 10'  
w/Bangboards
- Est Weight: 27,200 LBS

### ELECTRICAL

- DOT Approved LED Lighting System
- Amber Mid-Flashers
- Front Connector: 7-Way (SAE J560)
- Additional Front 6-Way Connector for Gate Control
- Rear 7-Way & 6-Way Connector for Pup (Lead)

### FRAME, GATES, & HOPPER

- 2-Axle Lead 40' OAL
  - Oscillating Fifth Wheel w/King Pin
  - King Pin Location: 18" (Standard)
  - Pintle Hook Installed Under Push Block
  - Drop Legs/Stiff Leg 4" X 4" Square
- 4-Axle Pup 24' OAL
  - Permanently Mounted Turntable w/Tandem Axle Dolly
  - Adjustable Draw Bar, 8'-12'; 12' Increments
  - 3" ID Pintle Eye
  - Dolly Jack
  - Aluminum Shed Plates at Front & Back
- 12" Wood Bangboards
- 18" AR450 Steel Wings
- Steel Front & Rear Fenders
- Hopper: 10 & 12GA (Standard Lightweight)
- 3/16 80W Steel Gates w/ Side Locks
- Removeable Push Block
- Tarp Brackets Installed for Cramaro Flip Tarp (Available Upon Request)

### UNDERCARRIAGE

- Hub Piloted 25k Axles: 1ABS 1 Non-ABS
- Spring Suspension
- Standard Galvanized Windrow Deflector
- 16 1/2" X 7" Cam Brakes
- HM 218248 & HM 212049 Bearings
- Meritor, Automatic Slack Adjusters
- Stemco Seals
- Tire Size: 385/65R22.5-14.9 W X 41.9 DI
- Outside Wheels: Aluminum

### AIR SYSTEM

- Twin 8" Cylinders w/60 Gal Air Tank, Oiler, Filter, & Quick Release
- Electric Cab Gate Controls
- Manual Gate Hand Controls from Ground
- Relay Valve Installed on Tank
- Quick Release Valve on Emergency Line

### PAINT & SAFETY

- Painted White
- Epoxy Primer w/Polyurethane Topcoat.
- Reflective Tape Conspicuity Striping

